

TCL



TCL BreezeIN 2.0 Series

Split System Air Conditioner

1.7KW | 2.6KW | 3.5KW | 5.3KW | 7.2KW | 8.2KW



KEY FEATURES

Cooling & Heating Capacities

Gentle Breeze Mode

Smart Airflow

Air Purification

Inverter Technology

"I Feel" Function

Turbo Function

Sleep Mode

Works with Google Assistant/
Amazon Alexa/TCL Home App

24Hr Timer

Eco Mode

5-Speed Fan

LED Display-On/Off

Easy Clean Design

Auto-Clean/Clean Reminder

Wifi Connectivity

T-AI Energy-Saving



Cooling




Heating



Gentle Breeze
Mode



Smart Airflow



Inverter
Technology

Learn more tcl.com/au

SPLIT SYSTEM AIR CONDITIONER SPECIFICATIONS

Model	Indoor/Outdoor Unit	TAC-06CHSD/VEIH	TAC-10CHSD/VEIH	TAC-13CHSD/VEIH	TAC-18CHSD/VEIH	TAC-24CHSD/VEIH	TAC-28CHSD/VEIH
Rated Values	Operation Type	Reverse Cycle	Reverse Cycle	Reverse Cycle	Reverse Cycle	Reverse Cycle	Reverse Cycle
	Cooling Capacity (KW)	1.78 (0.6~2.8)	2.64 (0.8~3.7)	3.5 (0.9~4.2)	5.3 (1.0~5.6)	7.2 (1.5~7.5)	8.2 (1.5~8.5)
	Heating Capacity (KW)	1.82 (0.6~3.5)	3.3 (0.6~4.4)	3.65 (0.8~5.2)	5.3 (1.0~5.8)	7.3 (1.5~7.8)	8.4 (1.5~8.5)
	Rated Input-Cooling (KW)	0.39	0.56	0.87	1.30	2.09	2.39
	Rated Input-Heating (KW)	0.37	0.75	0.85	1.22	1.83	2.30
	Moisture Removal (Litre/Hr)	0.60	0.80	1.10	1.80	2.20	2.80
	AEER	4.47	4.60	4.00	4.04	3.42	3.41
	ACOP	4.82	4.35	4.23	4.30	3.96	3.63
	Outdoor Operating Temperature Range	-15°C~52°C	-15°C~52°C	-15°C~52°C	-15°C~52°C	-15°C~52°C	-15°C~52°C
	Indoor Operating Temperature Range	16°C~31°C	16°C~31°C	16°C~31°C	16°C~31°C	16°C~31°C	16°C~31°C
Energy Star Rating for Cooling	Hot & Humid	6.0	6.5	5.5	4.5	3.5	3.5
	Mixed	4.0	5.0	4.5	4.0	3.0	3.0
	Cold	4.0	5.0	4.5	4.0	3.5	3.5
Energy Star Rating for Heating	Hot & Humid	3.0	3.5	3.5	3.5	3.5	3.5
	Mixed	2.5	3.0	3.0	3.0	3.0	2.5
	Cold	2.5	2.5	2.5	2.5	2.0	2.0
Noise	Indoor Unit dB (A)	49	54	54	60	64	65
	Outdoor Unit dB (A)	64	63	64	65	66	67
Refrigerant	Refrigerant (type/kg)	R32/0.410	R32/0.520	R32/0.630	R32/1.140	R32/1.140	R32/1.270
Piping	Liquid Pipe (mm)	Φ6.35(1/4")	Ø 6.35 (1/4")	Ø 6.35 (1/4")	Ø 6.35 (1/4")	Ø 6.35 (1/4")	Ø 6.35 (1/4")
	Gas Pipe (mm)	Φ9.52(3/8")	Ø 9.52 (3/8")	Ø 9.52 (3/8")	Ø 12.7 (1/2")	Ø 12.7 (1/2")	Ø 12.7 (1/2")
	Maximum Piping Length (m)	15	15	15	25	25	25
	Max Height Difference (m)	10	10	10	15	15	15
Product Dimensions	Indoor (W x D x H)	788×275×192mm	820 x 306 x 195mm	820 x 306 x 195mm	1097 x 332 x 222mm	1097 x 332 x 222mm	1097 x 332 x 222mm
	Outdoor (W x D x H)	787×290×498mm	795 x 305 x 549mm	795 x 305 x 549mm	927 x 380 x 699mm	927 x 380 x 699mm	978 x 421 x 803mm
Net Weight	Indoor (kg)	8	9	9	13	14	14
	Outdoor (kg)	21	23	24	37	38.5	45

For a more detailed specification sheet, please visit our website. Specifications and product images are subject to change without further notice.

⚠ Installation warning: Please ensure that all work is carried out by fully licensed and insured professionals in accordance with local regulations and manufacturers installation instructions.

ZERL Zoned Energy Rating Label - residential air conditioning star rating based on GEMS 2019 determination. Test conditions are based on AS/NZS3823.1.1.

HOW TO CHOOSE THE RIGHT ONE FOR YOU

